

CD200A COMBUSTIBLE GAS LEAK DETECTOR



Small, handy and easy-to-use gas leak detector for flammable gases. The 45 cm long and flexible gooseneck with illuminated sensor tip is ideal for finding leaks even in hard-to-reach places.

FEATURES

- Adjustable tick rate for fast leak detection
- Visual and audible alarm
- Precision Sensor
- Earphones
- Illuminated sensor tip for easy leak detection
- Fast response time (< 2 seconds for 40% LEL)
- Reliable and sophisticated technology
- Low weight
- Hard Carry Case

Gases	Acetone, alcohol, ammonia, butane, gasoline, natural gas, industrial
	Solvents, methane, propane, hydrogen sulfide, thinners and many
	combustible gases more.
	Please contact us for other gases.
Power Supply	4 AA batteries
Operating Time	approx. 12 hours
Sensor	Semiconductor
Warm-Up Time	approx. 1 minute
Sensitivity	< 50 ppm methane
Response Time	< 2 seconds to 40% LEL
Recovery Time	< 4 seconds of 40% LEL
Alarm Indicators	LEDs, Tickrate
Dimensions in mm	220 x 80 x 58 mm
Flexible Probe	450 mm
Operating Conditions	0 – 50°C / 10 – 90 % rh, non-condensing

IM Environmental Equipment Germany GmbH reserves the right to make technical changes.